


Head-worn microphone
Handsfree use
Lead and backing vocals



- Head-worn microphone with continuously adjustable behind-the-neck headband
- External shock mount for high mechanical-noise rejection
- Miniature gooseneck for precise positioning near the user's mouth
- Microphone arm provides choice of left or right-hand use



C 520

Head-worn condenser microphone with maximum dynamic range for **perfect vocal sound**. Its cardioid polar pattern effectively rejects unwanted ambient noise. An ideal choice for frontmen, singing keyboardists, drummers, guitarists, and dancers. The microphone arm mounts either on the **left or right side** of the headband as desired. The **C 520** provides the perfect solution for any performer needing a handsfree microphone.


A **transducer shock mount** reduces handling noise to a minimum. The **moisture shield** prevents perspiration from penetrating into the transducer element, ensuring a high degree of humidity protection for the microphone.

Versions

- C 520** for external phantom powering
- C 520 L** for use with the B 29 L battery power supply, AKG WMS Series bodypack transmitters, or the MPA V L adapter for external phantom powering.


Item numbers:

C 520	3066Z0001
C 520 L	3066Z0002



• Polar pattern:	cardioid
• Frequency range:	60 to 20,000 Hz
• Sensitivity:	5 mV/Pa (-46 dBV)
• Max. SPL for 1%/3% THD:	130/132 dB SPL
• Equivalent noise level (IEC 60268-4):	31 dB-A
• Signal/noise ratio (A-weighted):	63 dB
• Impedance:	<200 ohms
• Recommended load impedance:	≥2000 ohms
• Powering:	9 to 52 V phantom power to DIN 45596 or battery powering from B 29 L, or AKG bodypack transmitter
• Current consumption:	≤2 mA
• Connector:	C 520: 3-pin male XLR; C 520 ML: 3-pin mini XLR
• Cable:	C 520: 3 m (10 ft.); C 520 ML: 1.5 m (5 ft.)
• Finish:	matte black
• Dimensions:	length: 195 mm (7.7 in.); max. diameter: 134 mm (5.3 in.)
• Net/shipping weight:	C 520: 26 g (0.9 oz.) / 380 g (13.4 oz.) C 520 L: 26 g (0.9 oz.) / 260 g (9.2 oz.)
• Standard accessories:	W 44
• Optional accessories:	B 18, B 29 L, MPA V L

Head-worn microphone
for lectern
Handsfree use
Aerobics
Speech



- Head-worn microphone with continuously adjustable behind-the-neck headband
- Moisture shield
- Optimum audio and intelligibility even at high ambient noise levels
- Microphone arm provides choice of left or right-hand use



C 555 L


The new **C 555 L** head-worn microphone from AKG is rugged, extremely easy to use, and offers outstanding price/performance. The C 555 L is the ideal microphone for any **handsfree application** including gymnastics instruction, presentations, or onstage performance. The C 555 L rests securely and comfortably on the head, and can be attached to the left or right side of the behind-the-neck headband as desired.

A **transducer shock mount** reduces handling noise to a minimum. The **moisture shield** prevents perspiration from penetrating into the transducer element, ensuring a high degree of humidity protection for the microphone.

The C 555 L is the only version available and can be used with the B 29 L battery power supply, AKG WMS Series bodypack transmitters, or the MPA V L adapter for external phantom powering.

Item number:

C 555 L	3066Z0010
---------	-----------



• Polar pattern:	cardioid
• Frequency range:	80 to 20,000 Hz
• Sensitivity:	35 mV/Pa (-29 dBV)
• Max. SPL for 1%/3% THD:	126/130 dB SPL
• Equivalent noise level (IEC 60268-4):	22 dB-A
• Signal/noise ratio (A-weighted):	72 dB
• Impedance:	<200 ohms
• Recommended load impedance:	≥2000 ohms
• Powering:	9 to 52 V phantom power to DIN 45596 or battery powering from B 29 L, or AKG bodypack transmitter
• Current consumption:	≤ 2 mA
• Connector:	3-pin mini XLR
• Cable:	1.5 m (5 ft.)
• Finish:	matte black
• Dimensions:	length: 195 mm (7.7 in.); max. diameter: 134 mm (5.3 in.)
• Net/shipping weight:	26 g (0.9 oz.) / 260 g (9.2 oz.)
• Standard accessories:	W 444
• Optional accessories:	B 18, B 29 L, MPA V L