




102MX

2 Channel Stereo Audio Mixer



The **102MX** is a high-performance 2-channel stereo audio mixer for line level and mic level audio signals. It mixes one line level input with either a microphone or a second line level input and produces a mixed audio output signal.





102MX

FEATURES

- **S/N Ratio** - 69dB.
- **Input** - Line level 1 (or microphone) and line level 2.
- **Level (Gain) Control** - Line 1 (or microphone), line 2, and master level.
- **Selectable Microphone Input** - Dynamic or condenser microphone with bias voltage.
- **Talkover Button** - Microphone input signal mutes line audio output when a microphone detects sound.
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS: Mic/line 1: 10mV/1.6k Ω , 1Vpp/10k Ω , on 6.5mm phone connector; Line 2: 1Vpp/10k Ω , stereo on RCA connectors.

OUTPUTS: Line level, stereo, up to 5.6Vpp/150 Ω on RCA connectors.

BANDWIDTH (- 3dB): 100kHz.

GAIN RANGE: -12dB to 68.5dB (mic); -12dB to +8.8dB (line 1).

DIFF. PHASE: 0.05Deg.

S/N RATIO: 69dB.

CONTROL: Mic/line 1 level, line 2 level, master level rotary controls, condenser/dynamic mic, line/mic, talkover selection switches.

THD+NOISE: 0.018%.

2nd HARMONIC: 0.002%.

POWER SOURCE: 12V DC, 40mA.

DIMENSIONS: 12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.

WEIGHT: 0.25kg (0.55lbs) approx.

ACCESSORIES: Power supply, mounting bracket.

OPTIONS: RK-3T 19" rack adapter.