

TM-27



Given its multi-touch capability and a spacious screen size, the TM-27 is specified for professional multi-user interactive applications.

The TM-27, a multi-touch display built on state-of-the-art projected capacitive technology, enables users to navigate the display intuitively and precisely on a spacious screen. Highlighting its 10-point touch capability, multiple users can share the interactive experience on the same screen simultaneously. Its versatile inputs allow for effortless system integration. Leveraging a flexible dual-hinge stand, it provides height adjustability and a wide tilt range that optimise multi-user comfort and productivity. A combination of function and aesthetic, the TM-27 is suitable for a spectrum of interactive environments where efficiency is essential.

- > MVA panel provides consistent and accurate colour from all viewing angles
- > Incorporates Projected Capacitive Touch Technology
- > 10-point touch capabilities for systems with Microsoft® Windows® 7 and 8
- > LED-backlit technology with 1920 x 1080 Full HD resolution
- > Flush touch screen makes surface neat and clean
- > Connectivity: VGA, HDMI and DisplayPort
- > Built-in USB Port (USB 3.0) for easy connection with peripheral devices
- > HID compliant for easy integration without additional drivers
- > Integrated 2M-pixel webcam
- > Built-in speakers
- > Flexible dual-hinge stand design to maximise viewing comfort for multiple users
- > Tilt capacity from - 5° to 90°
- > VESA standard wall mount
- > Kensington® Security socket

TM-27


Specifications

TM-27

Panel	Panel Type	LED-Backlit TFT LCD (MVA Panel)
	Panel Size	27.0"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.311 x 0.311
	Brightness	270 cd/m2 (Typical)
	Contrast Ratio	1,000 : 1 (Typical)
	Viewing Angle (H/V)	178°/178°
	Display Colour	16.7 M
	Response Time (GTG)	6 ms (GTG)
Frequency (H/V)	H Freq.	30kHz – 83kHz
	V Freq.	55Hz -75Hz
Input	VGA	15-Pin D-Sub
	HDMI	HDMI
	DisplayPort	DisplayPort
USB Port	USB Port	USB 3.0 x 4
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø)
	Speaker	2 W x 2
Touch Screen	Technology	Projected Capacitive
	Panel Interface	USB (Type-B, HID compliant)
Web cam	Resolution	2 Mega-pixel
Power	Power Supply	Internal
	Power Requirements	100 ~ 240V, 50 - 60Hz
	Consumption	< 40W (On)
		< 5W (Stand-by) < 0.5W (Off)
Operating Conditions	Temperature	0°C ~ 40°C (32°F~104°F)
	Humidity	10% ~ 85% (No condensation)
Mounting	VESA FPMPMI	Yes (100mm x 100mm)
Dimensions	with Base (W x D x H)	660mm x 328.5mm x 454mm (26.0" x 12.9" x 17.9")
	Packaging (W x H x D)	753mm x 204mm x 527mm (29.6" x 8.0" x 20.7")
Weight	Product Weight (with base)	11.0 kg (24.2 lbs)
	Packaging Weight	12.8 kg (28.2 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, RoHS, GOST-R, WEEE, REACH
Accessories	Supplied	CD ROM (user manual), warranty card, power cord, 15-Pin D-Sub cable, USB cable, Audio cable



Integration of 10-point touch and projected capacitive touch technology provides accurate and precise touch experience



Flexible dual-hinge stand design to maximise viewing comfort for multiple users



Versatile connectivity: VGA, HDMI, DisplayPort and USB port allow for effortless system integration



MVA panel provides superb clarity from all viewing angles

