

PLC-XU74

Brilliant Ideas for Your Business.

SANYO

- Resolution, native: XGA (1,024 x 768), maximum: UXGA (1,600 x 1,200)
- Brightness: 2,500 ANSI lumens
- Light weight of only 2,4 kg
- Key lock function, pin code lock
- Direct Power On/Off
- Low fan noise: 29 dB (Eco Mode)
- Presentation Kit
- On-screen menu in 16 different languages
- 3-year warranty, 1 year lamp warranty



PLC-XU74

Brilliant Ideas for Your Business.

SANYO

TECHNICAL DATA	PLC-XU74
Category	Business & education
Panel	3 x 0.6" TFT p-Si (4 : 3)
Projection Lamp	200 W UHP (LMP-106)
Brightness in ANSI lumens	2,500
Lamp Service Life	3,000 h (Eco Mode)
Fan Noise	29 dB (Eco Mode)
Standard Lens	F = 1.65 – 1.81/f = 22.5 – 27 mm
Aspect Ratio	1.78 – 2.14 : 1
Throw Distance	1.43 – 12.6 m (image size 81 x 61 – 610 x 457 cm) (You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances.)
Contrast Ratio	450 : 1 (auto mode)
Resolution in Pixels	1,024 x 768 (XGA)
Horizontal Resolution	600 TV lines
Uniformity	85 %
Bandwidth/Frequency	140 MHz, horizontal 15 ~ 100 kHz, vertical 50 ~ 100 Hz
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB/component/SCART-RGB), (component/SCART-RGB with corresponding adapter cable, see "Optional Accessories"), 3.5 mm stereo jack Input 2: D-Sub15 (RGB) or Monitor Out; Audio: shared with Input 1 Input 3: 1 x RCA (video), mini DIN 4-pin (S-video); Audio: 2 x RCA (R, L mono) Audio Output: 3.5 mm Stereo Jack (variable) Control Input 1: Mini DIN 8-pin (RS232) Control Input 2: USB Type B
Audio Function	1 W Mono
Keystone Correction	Vertical +/-20°
Lens Shift / U/D Ratio	9 : 1 (Fixed U/D Ratio)
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA/Mac
Zoom/Focus	1.2 times/manual
Power Consumption/Voltage	275 W/100 – 240 V
Warranty	3 years, 1 year lamp
Dimensions (W x H x D)	294.5 x 69.5 x 208 mm
Weight	2.4 kg
Standard Accessories	IR remote control, batteries, manual, DVI-D-Sub15 cable, lens cover with fastener and cord, power cable
Optional Accessories	Component/D-Sub15 cable (POA-CA-COMPVGA), SCART/D-Sub15 cable (POA-CA-SCART), presentation kit (POA-RC KIT02), remote control with laser pointer (POA-RC KIT03), replacement lamp, carrying case
Lenses	Standard Lens



Technical specifications subject to change without notice. Date 09/2006

