ME40A · ME46A · ME55A

40" • 46" • 55" Commercial LED LCD Displays L≡⊃

It gives you commercial TV and digital content options. And more control over both.





Integrated TV Tuner Displays broadcast TV.



Lower TCO

LED technology consumes an average of 40% less power, for lower total cost of ownership. LED technology also contains no mercury, which is easier on the environment.



High-Definition Picture

LEĎ backlight, 1920 x 1080 Full HD resolution, 16:9 widescreen, 5000:1 contrast ratio and 178° horizontal and vertical viewing angles deliver amazing images.



Ultra-Slim 29.9mm (1.18") Chassis

The stylishly thin chassis helps simplify installation, and makes it suitable for most locations.



Thin Rezelo

The thin side bezels of 15.1mm (0.59") on the ME40A and 14.6mm (0.57") on the ME46A add sophisticated good looks and make more seamless video walls.



MagicInfo Lite

Samsung software lets you plug-and-play content with a USB thumb drive loaded with PowerPoint* files, videos, images or more, and quickly schedule content in a matter of minutes.



RS232C and RJ45 Ports

Makes display control simple.



DisplayPort and HDMI

Makes connectivity easy.



3-Year Warranty

Longer protection with greater reliability than consumer TVs.

The ME Series delivers a high-resolution display and integrated TV tuner, with easy display control through RS232C and RJ45 ports. An average lower power consumption of 40% lowers total cost of ownership and is easier on the environment. And the ultra-slim chassis with slim bezel design will look attractive anywhere you want your message to be seen. **Business. Innovated.**



ME40A • ME46A • ME55A Commercial LED LCD Displays







KEY SPECIFICATIONS

For complete product specifications, visit samsung.com/prodisplay

| Product | Model Number | | ME40A | ME46A | ME55A |
|---------------|------------------------------------|-------|---|---|---|
| Display | Screen Size | | 40" | 46 | 55" |
| | Panel Technology | | 60Hz LED BLU | 60Hz Edge-lit LED LCD | 120Hz Edge-lit LED LCD |
| | Resolution | | 1920 x 1080 (16:9) | 1920 x 1080 (16:9) | 1920 x 1080 (16:9) |
| | Brightness | | 300nit | 300nit | 380nit |
| | Contrast Ratio (Typical/Dynamic) | | 5000:1 | 5000:1 | 5000:1 |
| | Viewing Angle | | 178°/178° | 178°/178° | 178°/178° |
| | Response Time | | 8ms | 8ms | 8ms |
| Connectivity | Input | | VGA (D-sub 15 pin), DVI-D, HDMI, DisplayPort, Component/ Composite, USB, Stereo Mini Jack, TV In | VGA (D-sub 15 pin), DVI-D, HDMI, DisplayPort, Component/ Composite, USB, Stereo Mini Jack, TV In | VGA (D-sub 15 pin), DVI-D, HDMI, DisplayPort, Component/ Composite, USB, Stereo Mini Jack, TV In |
| | Output | | DVI-D (Digital Loop out), Stereo Mini Jack | DVI-D (Digital Loop out), Stereo Mini Jack | DVI-D (Digital Loop out), Stereo Mini Jack |
| | External Control | | RS232C (in/out) thru stereo jack, RJ45 | RS232C (in/out) thru stereo jack, RJ45 | RS232C (in/out) thru stereo jack, RJ45 |
| | Sensor | | Stereo Mini Jack (IR in/out), Mini USB (Ext. Brightness/IR Sensor) | Stereo Mini Jack (IR in/out), Mini USB (Ext. Brightness/IR Sensor) | Stereo Mini Jack (IR in/out), Mini USB (Ext. Brightness/IR Sensor) |
| Power | Power Supply | | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz | AC 100 - 240 V~ (+/- 10 %), 50/60 Hz |
| | Power Consumption Typical/Max | | 100W / 120W | 140W / 160W | 160W / 180W |
| | Power Consumption Standby | | Less than 1W | Less than 1W | Less than 1W |
| Environmental | Operating Temperature | | 0°C - 40°C | 10°C - 40°C | 10°C - 40°C |
| Conditions | Operating Humidity | | 10%~80% Non-Condensing | 10%~80% Non-Condensing | 10%~80% Non-Condensing |
| Features | Special | | Built-in TV tuner, Built-in Speaker (10W + 10W), Simple Plug & Play media player (thru USB), Built-in MagicInfo Lite signage software, Narrow bezel, Slim chassis depth (1.18") | Built-in TV tuner, Built-in Speaker (10W + 10W), Simple Plug & Play media player (thru USB), Built-in MagicInfo Lite signage software, Narrow bezel, Slim chassis depth (1.18") | Built-in TV tuner, Built-in Speaker (10W + 10W), Simple Plug & Play media player (thru USB), Built-in MagicInfo Lite signage software, Narrow bezel, Slim chassis depth (1.18") |
| | Built-in Tuner | | Yes | Yes | Yes |
| | Media Player Type | | USB thumb drive plug/play feature with MagicInfo Lite signage software, External Media Player (optional setback box, SBB-A) | USB thumb drive plug/play feature with MagicInfo Lite signage software, External Media Player (optional setback box, SBB-A) | USB thumb drive plug/play feature with MagicInfo Lite signage software, External Media Player (optional setback box, SBB-A) |
| | VESA Standard Wall-Mount Interface | | 200 x 200mm | 400 x 400mm | 400 x 400mm |
| Dimensions | Product Dimension | | Without Stand: 36.2" (W) x 21.1" (H) x 1.18" (D) | Without Stand: 41.5" (W) x 24.1" (H) x 1.18" (D) | Without Stand: 49" (W) x 28.2" (H) x 1.18" (D) |
| | Shipment Dimension | | 40.8" (W) x 24.9" (H) x 5.9" (D) | 46.1" (W) x 28.7" (H) x 7.8" (D) | 53.7" (W) x 33.4" (H) x 7.8" (D) |
| | Bezel Width | | 15.1mm (Bottom 16.6mm) | 15.1mm (Bottom 16.6mm) | 15.1mm (Bottom 16.6mm) |
| Weight | Product Weight | | 23.1 lbs. | 27.5 lbs. | 37.6 lbs. |
| | Shipment Weight | | 28.4 lbs. | 36.5 lbs. | 48.8 lbs. |
| Service | Standard Waranty | | 3 Years Onsite Parts and Labor | 3 Years Onsite Parts and Labor | 3 Years Onsite Parts and Labor |
| Accessories | Included | | Quick Setup Guide, Warranty Card, Application CD, D-Sub cable, Power Cord, Remote Controller, Batteries | Quick Setup Guide, Warranty Card, Application CD, D-Sub cable, Power Cord, Remote Controller, Batteries | Quick Setup Guide, Warranty Card, Application CD, D-Sub cable, Power Cord, Remote Controller, Batteries |
| | Optional | Mount | WMN4070SD WMN2000AD | WMN4270SD WMN2000BD | WMN4270SD WMN2000BD |
| | | Stand | STN-L4055AD | STN-L4055AD | STN-L4055AD |

GREEN MANAGEMENT

| Emission Standard | EMC | EMC | EMC |
|----------------------------|------------------------------|------------------------------|------------------------------|
| Energy Star® 5.0 Compliant | | | |
| ROHS Compliant | | | |
| Packaging Recyclability | Packing Materials Recyclable | Packing Materials Recyclable | Packing Materials Recyclable |

CONNECTIVITY

| 1. | DVI | In |
|----|-----|----|
| 2. | Ant | In |

8 Audio Out 9. RGB/DVI/DP/HDMI Audio In

3. RGB/VGA In

10. USB 11. Component

4. RS232C 5. RJ45/LAN

6. IR/Ambient Sensor In

12. DisplayPort

7. IR Out

13. HDMI In 14. DVI Out (Loop out)





For complete product information, visit samsung.com/prodisplay or samsung.com/business

