



The Versatile 10.4" Metal Frame TFT LCD Monitor



QUALITY SYSTEM
REGISTERED TO
ISO 9001:2000

MODEL NO.	HI-10W12U	HI-10Y12U	HG-10W12U
Viewing area	10.4"		
Touch Panel	NO	YES(ELO)	NO
Strengthen Glass	NO	NO	YES NEW
Pixel Pitch	0.264 X 0.264 mm		
Resolution	800 X 600 SVGA		
Effective display area	211.2 X 158.4mm		
Color	262,144		
Response time(tr/TF)	20/30ms		
Contrast ratio	250:1		
Brightness	250 cd/m ²		
View angle	T:30° B:10° L:40° R:40° (Min.)		
Backlight	1CCFL		
Lamp Life	20000hrs (Typ.)		
Input Signal	Analog VGA & Video(Composite Video System PAL/NTSC/SECAM)		
Input Connector	D-Sub 15Pin, RCA / BNC Jack, S-VHS Din Type		
Scan frequency	H:31.5~53KHz / V:56~85Hz		
Control	OSD		
Power adaptor input	Universal AC 100~240 V, 50/60Hz		
Adaptor output	DC 12V / 2A		
Power Management	VESA DPMS Standard		
Consumption	18W / Stand by 2.5 w		
Operating Temperature/Humidity	0 ~ 40 °C / 10 ~ 85%RH		
Storage Temperature/Humidity	-20 ~ 60 °C / 10 ~ 90%RH		
Sync Signal	TTL Level +/- Polarity		
Scanning	Non-Interlace		
Dimension (mm)(WxHxD)	270 x 200 x 46		
Net Weight(Kg)	2	2.3	
Safety & EMI	CE (EMC+LVD)		
Vibration	10Hz / One-way 1m/m		
Pixel (MHz)	56.25 MHz		
Content	LCD Monitor, Key Pad, Power Adaptor, VGA Cable		

