

Feature-Rich, Full HD Video Is Here

LifeSize® Express 220™

LifeSize Express 220 is a Full HD video communications system that is both affordable and scalable. Ideal for small working groups, teams or individual knowledge workers who want to take communication over distance to the next level, LifeSize Express 220 has it all.

With LifeSize Express 220, you not only get Full HD video quality—1080p30/720p60—for natural, realistic interactions at the lowest possible bandwidth but also crisp, crystal clear data sharing and an all new digital I/O with Full HD support, plus dual HD displays, Full HD camera, and phone or LifeSize MicPod options.

Combined with the LifeSize® Phone™, 2nd Generation, LifeSize® Camera 10x™ and LifeSize® Digital MicPod™, you have the most full-featured video conferencing solution available today. The LifeSize Phone brings touch-screen simplicity to the conference room and eliminates the need for a separate remote control. Users can share content, control cameras, change layouts, add callers and do so much more with ease.

LifeSize Express 220 brings people together by allowing them to interact successfully across distances. Seeing facial expressions, body language and gestures makes you feel truly connected and understood.

And just like all of the products in the LifeSize 220 Series, LifeSize Express 220 features:

- › Highest available resolution on the market—1080p30
- › Unprecedented bandwidth/performance
- › Adaptive motion control with forward error correction
- › Streaming and recording of point-to-point calls

HD quality. Simplicity. Meaningful team connections. LifeSize Express 220 is clearly how video communications are meant to be.



LifeSize Express 220 At-a-Glance

Video Quality	<ul style="list-style-type: none"> • Full HD • Standards-based • 1920x1080-30fps • 1280x720-60fps
Multiple HD Monitors	Supports up to two HD monitors
HD Camera	Supports HD pan-tilt-zoom camera
Manage HD Video & Audio	Control video, audio and data sharing with the touch-screen interface of LifeSize Phone, 2nd Generation
HD Video Communications	Make point-to-point calls or join multipoint calls
Free video-based training	www.lifesize.com/ask

System Components

LifeSize codec
 HD PTZ LifeSize Camera 200 or LifeSize Camera 10x
 LifeSize MicPod or LifeSize Phone, 2nd Generation
 Wireless remote control
 Power supply/cables

Communications

H.323, SIP, 128 Kbps–4.0 Mbps
 1xRJ-45 Network LAN
 1x3.5 mm Mic In for LifeSize MicPod
 1 x RJ-45 for LifeSize Phone, 2nd Generation or LifeSize Networker (optional)

Support for Multiple Displays

Any HD displays supporting HDMI or DVI-I input
 For additional information on displays, visit:
www.lifesize.com/support

HD 1080p30/720p60 PTZ Camera

Wide-angle zoom lens with 70 degree field of view
 Up to 4x/10x optical zoom on LifeSize Camera 200/10x
 Auto focus/automatic gain control
 10 camera presets (near or far end)
 Standard 3.0 M HDMI cable

Video Specifications/Video Resolutions

Maximum resolutions widescreen 16:9 aspect ratio
 All resolutions progressive scanning
 All resolutions at 30 frames per second except 60 frames per second where noted
 384 Kbps (912x512 pixels) DVD resolution
 512 Kbps (1024x576 pixels)
 768 Kbps (1280x720 pixels) high definition
 1.1 Mbps (1280x720 pixels @ p60) high definition
 1.7 Mbps or higher (1920x1080pixels) high definition

Video Standards

H.261, H.263, H.263+, H.264 and H.239 and BFCP compliant with Polycom®
 Support for multiple dual live-streaming modes: 1080p30 and 720p5; 720p60 and 720p5; 720p30 and 720p30

Video Inputs (2 Inputs)

1 x HD Video In (1080p30/720p60)
 1 x DVI-I In (HDMI/VGA enabled)

Video Outputs (2 Outputs)


2 x HD digital video out (1080p30/720p60)

Fully Integrated, HD Audio Conference Phone

90 Hz up to 16 kHz
 Powered by codec directly through cable
 Touch-screen user interface
 Manage both HD video and audio
 Support for up to two LifeSize Digital MicPods (additional purchase)

Audio Standards

G.711, G.722, G.722.1 and G.722.1C licensed from Polycom, G.728, G.729, MPEG-4-AAC-LC



Audio Features

GIPS NetEQ packet loss concealment
 Full duplex for natural conversations
 Echo cancellation for echo-free calls
 Automatic gain control
 Automatic noise reduction
 Three-way audio add-on call capability
 LifeSize MicPod or dual MicPod support (optional)

Audio Inputs (5 Inputs)

1 x Line In (L+R) (3.5mm)
 1 x Mic In—two channel (3.5mm)
 1 x RJ-45 (LifeSize Phone, 2nd Generation) (optional)
 1 x HD Video In
 1 x DVI-I In

Audio Outputs (4 Outputs)

1 x Line Out/Headset (L+R)
 1 x RJ-45 (LifeSize Phone, 2nd Generation) (optional)
 2 x HD Video Out

Other Supported Standards

H.221, H.224, H.225, H.231, H.241, H.242, H.245, H.281,BONDING (ISO13871) via LifeSize Networker, RFC 3261,RFC 3264, RFC 2190, RFC 3407, RFC 2833

User Interface & Features

Context-sensitive user interface
 Graphical user interface call manager
 Multiple languages supported
 Do Not Disturb mode
 RS-232 serial pass-through support

Stream/Record with LifeSize® Video Center™

Record/stream outside of a call
 Record/stream point-to-point or multipoint calls
 Capture all call participants (near or far)
 Auto-record all calls
 Single button, ad-hoc recording
 Recording indicator

Security

Admin and user-level password
 SNMP security alerts
 Ability to disable HTTP, SSH and Telnet services
 H.235 (AES) encryption support including strict compliance
 TLS/SRTP support
 IEEE 802.1x support
 Kensington Security Slot

Intelligent Networking Features

Adaptive motion control (AMC) including forward error correction (FEC)
 NAT/firewall traversal (H.460/SIP)
 IPv4 and IPv6 support
 Auto bandwidth detection
 ISDN support via LifeSize Networker

Directory and Address Book

Up to 1,000 local directory entries
 Save, lock, remove, redial list features
 Missed call notification
 Auto-discovery directory lookup (patent pending)
 LDAP support/H.350 compliant
 Meetings directory support
 H.323 URI dialing support (Annex O)

System Management

Out-of-box setup via web interface and management tool
 SNMP
 Backup and restore capability
 JPEG snapshots through web interface

Power

AC voltage 100–240V, 50–60 Hz, 2.5A via external power supply

Environmental Data

Operating temperature: 0°C (32°F) to 40°C (104°F)
 Operating humidity: 15% to 85%, noncondensing
 Storage temperature: –20°C (–4°F) to 60°C (140°F)
 Storage humidity: 10% to 90%, noncondensing

Codec Dimensions

Width: 288 mm (11.34")
 Depth: 187.5 mm (7.38")
 Height: 41.3 mm (1.63")
 Weight: 1.29 Kg (2.84 lbs)

Regulatory Model Number

LifeSize Express 220 = LFZ-018



Microsoft® qualified with Microsoft® Office Communications Server 2007 R2™ and interoperable with Microsoft® Lync®



Headquarters

Austin, Texas, USA
 +1 512 347 9300
 Toll Free US +1 877 543 3749

EMEA Regional Office

Munich, Germany
 +49 89 20 70 76 0
 Toll Free Europe +00 8000 999 09 799

www.lifesize.com
 E-mail info@lifesize.com

APAC Regional Office

Singapore
 +65 6303 8370



Delivering the Ultimate Communication Experience

© 2013 Logitech. All rights reserved. Information contained in this document is subject to change without notice. LifeSize is the registered trademark or trademark of Logitech. All other trademarks are the property of their respective owners.

DS_Express220_EN_0413