



SIXBAR 1000™

SKU# SIX086

The new SIXBAR 1000™ features (12) 12W 6-IN-1 RGBAW+UV LEDs, 30° beam angle, individual control of each LED, variable dimming curve modes, strobe and chase effects, a UV wavelength of 395nm, ArtNet, KlingNet and RDM (remote device management) protocol support, 3pin and 5pin DMX, powerCon, and RJ45 in/out connections, LCD menu display with 4 button control panel, integrated dual rigging brackets, multiple unit power linking, rugged die-cast aluminum exterior, flicker free operation for TV and FILM, 145W max power consumption, and a multi-voltage universal auto switching power supply (110-240v).



FEATURES

- 12 x 12W 6-in-1 RGBAW+UV LEDs
- 30° Beam Angle
- UV Wavelength 395nm
- ArtNet and KlingNet Protocol Support
- RDM (Remote Device Management)
- Individual Control of Each LED
- Variable Dimming Curves
- Strobe and Zone Chase Effects
- Integrated Dual Rigging Brackets
- Multiple Unit Power Linking
- Rugged Die-Cast Aluminum Exterior
- Flicker Free Operation for TV and FILM



Frost Filter and Glare Shield Included

PRODUCT SPECIFICATIONS

SOURCE

(12) 12W 6-in-1 RGBAW+UV LEDs
100,000 Hour Average LED Life*

*LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

8,500 LUX 790 FC @3.3' (1m) (30° Full ON)
3,660 LUX 340 FC @6.6' (2m) (30° Full ON)
2,040 LUX 190 FC @9.8' (3m) (30° Full ON)
1,290 LUX 120 FC @13.1' (4m) (30° Full ON)
878 LUX 82 FC @16.4' (5m) (30° Full ON)

EFFECTS

Strobe and Chase Effects
Individual LED Control
Variable and Selectable Dimming Curves

CONTROL / CONNECTIONS

8 DMX Channel Modes (6 / 7 / 11 / 13 / 36 / 72 / 75 / 79)
4 Button Control Panel and LCD Menu Display
ArtNet + KlingNET Protocol Support
RDM (Remote Device Management)
(2) etherCON Ports
3pin and 5pin DMX In/Out
powerCON Power In/Out

SIZE / WEIGHT

Length: 35.4" (900mm)
Width: 8.1" (206.4mm) *with included shield
Vertical Height: 6.1" (155mm)
Weight: 16.0 lbs. (7.3 kg)

ELECTRICAL / THERMAL

AC 110-240V - 50/60Hz
145W Max Power Consumption
Power Linking: 6pcs @110V / 15pcs @240V
5°F to 113°F (-15°C to 45°C)
UV Wavelength: 395nm

APPROVALS / RATINGS


CE | cETLus | IP20



INCLUDED ITEMS

powerCON Cable
Frost Filter
Glare Shield




PHOTOMETRIC DATA



SIXBAR 1000

30° Beam Diameter	m 1		m 2		m 3		m 4		m 5						
	ft 3.3	ft 6.6	ft 9.8	ft 13.1	ft 16.4	lux	fc	lux	fc						
Distance	1	2	3	4	5	8,500	790	3,660	340	2,040	190	1,290	120	878	82
Photometrics	lux	fc	lux	fc	lux	fc	lux	fc	lux	fc	RED LEDs	1,080	100	490	46
											GREEN LEDs	2,140	199	1,030	96
											BLUE LEDs	2,430	226	1,179	110
											WHITE LEDs	2,700	251	1,240	115
											AMBER LEDs	1,065	99	490	46
											UV LEDs	590	55	255	24
											FULL ON	8,500	790	3,660	340

DIMENSIONAL DIAGRAMS



OPTIONAL ACCESSORIES

ORDER CODE	ITEM
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
EWDMSYSTEM	Wireless DMX System (1 Transmitter, 1 Receiver)
EWDMXT	Wireless DMX Transmitter
EWDMXR	Wireless DMX Receiver
AC3PDMX5PRO	5 ft. (1.5m) 3pin PRO DMX Cable
AC5PDMX5PRO	5 ft. (1.5m) 5pin PRO DMX Cable
PLC3	3' (1m) PowerCON PRO Link Cable
CAT005	5' (1.5m) CAT6 Ethercon Cable
	Additional cable lengths available

