

Uniko S

Indoor LED poster
2.9 mm pixel pitch



- One-person easy-handling for setup
- Vertical & Horizontal installation
- Ultra-slim and light weight
- Just Plug & Play
- Wi-Fi easy connection
- IOS & Android dedicated app



Indoor LED advertising totem

A smart solution for commercial signs.



wi-fi connection

Main performance

Thin lightweight and effective. A communication world in only 25 kg; real-time messages and graphics editing thanks to an easy and intuitive dedicated IOS and Android app.
Just plug and PLAY!

Mechanical quality

- Lightness
- Easy to install
- Vertical and horizontal installation

European certification
standards guaranteed



RoHS LVD



DATA PARAMETER

	UK-2.9S
Pixel pitch (mm)	2,9mm
LED Type SMD 3in1	SMD2020
Pixel m2	112.896
Unit dimension (mm) WxHxD	500x1926x56
Screen dimension mm	476x1904
Screen Resolution (pixels)	160x640
Unit weight (Kg)	25
Refresh Rate (Hz)	1200 - 2400
Signal Processing	14 - 16 bit
Colour Range	281 Trillion Colours
Luminance uniformity	≥ 97%
Colour Temperature	3500K - 9500K ±500
Contrast ratio	2500:1
Horizontal Viewing Angle (Deg)	130
Vertical Viewing Angle (Deg)	130
Brightness (cd/ m2)	1200
Power Cons. Max	490
Power Cons. AWG	200
Operating temperature (C°)	-20 to 60
Ambience humidity	90% at 25C°
IP Protection Front / Back	IP32 / IP32
Lifetime (60% Brightness)	100.000 h
MTBF	≥ 10.000 hours
Data Transfer Method	RJ45 max 70m - Optical Fiber >70m
Power Supply	AC 220-240 V, 50/60 Hz
Certifications	CE - LVD - EMC - RoHS

