

# PIXEL TUBE

# **DATASHEET**



Colours

**RGBW** 

Total LED power

28W

Luminous Flux

6951 m

Strobe

0-25H

Beam Angle

180°

Pixels

16

# Electrical

### Battery

LG Chem Lithium-ion

### **Battery Lifetime**

70% after 300 cycles

### **Battery Runtime**

Up to 20 hou

### LED Lifetime

50.000 Hours

### Charging time (nominal)

/ Hours

### Input Voltage (Charger)

90-264V 47-63Hz

### Input Voltage (Light)

48V 0.5A

# Control

### Wireless Modules

865-870MHz 902-928MHz

### Range

300m | 330 Yards

### DMX

Supports CRMX and W-DMX



# Construction

#### Housing

Polycarbonate, metal end caps

### IP Rating

IP65

#### Relative humidity

0-100%

### Operating Temperature

0-40 °C

#### Weight

1kg

2.2Lbs

### Dimensions

Ø42 x 1035mm Ø1.6" x H40.7"

### Accessories



### Charger

AX1-CHR (Included)



### Eyebolt

AX1-EBLT (2 pces Included)



### Holder

AX1-H (2 pces Included)



#### Stand

AX1-STD (Included)





Charging case

AX1-CHRCSE



Spigot (3/8" & 1/4"-20 threads) AX1-BLT





А	ON/OFF Button
В	Screws
С	Rubber Charging socket
D	Charging socket
E	M5 Thread for Screw Hooks

Ø1035mm (Ø40.7")

Ø42.6mm (Ø1.6")